

MANUAL GREASE PUMPS



Ease of operation
T-handle pump provides up to 60 shots of grease per prime

Leak free connection

Positive no leak connection ensures grease reaches the required area

Easily switch between high pressure/high volume

PRESSURITE™ gun offers both high volume or high pressure switching for quick and easy greasing

Kink free delivery hose

360° ball swivel to prevent hose from kinking

Easy access to hard to reach places

10' long hose provides easy access to hard to reach grease nipples

Suitable for different height grease pails

Sliding bung adapter allows the pump to adjust to different height grease containers

Contamination free greasing

Rubber-edged follower plate keeps grease clean and prevents air pockets



SUPERLUBE™ GREASING SYSTEM

K4-01

The SUPERLUBE™ greasing system is an economical and compact solution for portable high-volume/high-pressure manual greasing. An easy push down T-handle provides up to 60 shots of grease per prime.

This system is designed for applications where compressed air is unavailable and bulk grease is preferred.

The SUPERLUBE™ has a fully repairable sealed system providing an inbuilt grease strainer which prevents grease contamination and contributes to a much longer service life.

TECHNICAL SPECIFICATIONS

- High volume delivery pressure up to 345BAR / 34,450kPa (5,000psi)
- High pressure delivery pressure up to 689BAR / 68,900kPa (10,000psi)
- Provides up to 60 shots of grease with each prime
- Up to 0.45g (0.015oz) per shot (High pressure setting)
- Up to 1.25g (0.044oz) per shot (High volume setting)
- Pail size range: 16 – 25kg (35 - 55lb)
- Maximum viscosity: Up to NLGI 2
- Wetted parts: aluminium, steel, nitrile rubber
- 3m (10') Flexible delivery hose
- **KY:** SUPERGRIP™ high pressure grease coupler

REPAIR KITS

- **K4-1K:** Overhaul Kit